



1 / 23

FIG. 1




2 / 23

FIG. 2




3 / 23

FIG. 3




4 / 23

FIG. 4




5 / 23

FIG. 5




6 / 23

FIG. 6




7 / 23

FIG. 7




8 / 23

FIG. 8



9 / 23

FIG. 9



T_{IDT} : Initial delay time. $T_{IDT} > 4096/f_c$

T_{TRFW} : RF waiting time. $512/f_c$

n : randomly generated number of Time Periods for T_{TRFW} .


$0 \leq n \leq 3$

T_{IRFG} : Initial guard-time between switching on RF field and start to send command or data frame.

$T_{IRFG} > 5 \text{ ms}$

10 / 23

FIG. 10



T_{ADT} : Active delay time, sense time between RF off Initiator/Target and Target/Initiator.


($768/f_c \leq T_{ADT} \leq 2559/f_c$)

T_{RFW} : RF waiting time. ($512/f_c$)

n : Randomly generated number of Time Periods for T_{RFW} . ($0 \leq n \leq 3$)

T_{ARFG} : Active guard time between switching on RF field and start to send command. ($T_{ARFG} > 1024/f_c$)

FIG. 11




12 / 23

FIG. 12


COMMAND/RESPONSE
ATR_REQ
ATR_RES
WUP_REQ
WUP_RES
PSL_REQ
PSL_RES
DEP_REQ
DEP_RES
DSL_REQ
DSL_RES
RLS_REQ
RLS_RES

FIG. 13




14 / 23

FIG. 14




15 / 23

FIG. 15




16 / 23

FIG. 16




17 / 23

FIG. 17




18 / 23

FIG. 18




19 / 23

FIG. 19




20 / 23

FIG. 20




21 / 23

FIG. 21



22 / 23

FIG. 22



23 / 23

FIG. 23

